

Description	Gauge	Diameter	Coil Break Range	Tensile Strength
Baling Wire, Soft Annealed, Black Oiled	10 Ga	0.135 in	930 to 1073	65,000 - 75,000 psi
Baling Wire, Soft Annealed, Black Oiled	11.5 Ga	N/A	N/A	65,000 - 75,000 psi
Baling Wire, Soft Annealed, Black Oiled	11 Ga	0.121 in	747 to 862	65,000 - 75,000 psi
Baling Wire, Soft Annealed, Black Oiled	12 Ga	0.105 in	563 to 649	65,000 - 75,000 psi
Baling Wire, Soft Annealed, Black Oiled	13 Ga	0.091 in	423 to 488	65,000 - 75,000 psi
Baling Wire, Soft Annealed, Black Oiled	14 Ga	0.080 in	327 to 377	65,000 - 75,000 psi
Baling Wire, Soft Annealed, Black Oiled	8 Ga	0.165 in	1389 to 1603	65,000 - 75,000 psi
Baling Wire, Soft Annealed, Black Oiled	9.5 Ga	0.142 in	1029 to 1187	65,000 - 75,000 psi
Baling Wire, Soft Annealed, Black Oiled	9 Ga	0.144 in	1058 to 1221	65,000 - 75,000 psi